


Suction & Discharge
 Cold Weather/Flexible
 Heavy-Duty
 Abrasion Resistance
 Petroleum
 Food Grade
 Duct
 Specialty
 Accessories

Kanaline Blue

Heavy-duty water suction and discharge hose for applications requiring combined vacuum, higher working pressures, and increased flexibility



SPECIFICATIONS

- Temp. Range:** -40°F to 140°F
- Applications:** Heavy-duty suction and discharge with increased flexibility for use in colder environment applications, where more flexibility is desired, and liquid fertilizer
- Construction:** Flexible cold weather PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.
- Features:** Lightweight and flexible. External helix provides for easy drag. Rated for both suction and discharge. Clear sidewall permits visual check of material flow.
- Note:** Banding coil must be used for all sizes.

AVAILABLE SIZES

Inside Dia. Inches	Outside Dia. Inches	Pitch Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In Hg	Weight Lbs/Ft	Standard Length Ft
1-1/2	2.10	0.37	2.0	75	28.0	0.47	60,100
2	2.60	0.43	3.0	70	28.0	0.70	60,100
3	3.70	0.59	5.0	70	28.0	1.13	60,100
4	4.80	0.63	7.0	60	28.0	1.74	60,100
6	7.30	0.98	9.0	50	28.0	3.88	60,100
8	9.50	1.07	15.0	40	28.0	5.54	15,20,25
10	11.63	1.22	24.5	30	28.0	8.68	20,25,40

