





STYLE: Stepladder



• External Pinch-Proof[™] spreaders on 3', 7', 8' and 10' models

SPECIFICATIONS

Approx. Shipping

Wt. Lbs.

Model No.	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.
373	3'	17-3/4"	23-3/8"	1.5	9.0
374	4'	19-1/2"	29-1/2"	2.1	11.0
375	5'	21-1/4"	35-3/4"	2.8	13.5
376	6'	23"	41-7/8"	3.5	15.5
378	8'	26-1/2"	54-1/4"	5.1	22.5
310	10'	30"	66-1/2"	7.0	31.0

DIMENSIONS

Тор:	5-1/8" x 12-1/8"	Steps:	3" wide
Front Rails:	3" wide	Rear Rails:	1-1/4" wide
Front Flange:	7/8" wide	Rear Flange:	1" wide

• Internal spreaders on 8' and above

Model

No.

Height (Size)

to Platform

Rail

Length

SPECIFICATIONS NOTE: Type IAA duty rating is for platforms ranging in size from 4' to 8'

Approx.

Spread

Approx. Cu. Ft.

Per Unit

Approx.

Width

P404	4'	6'	24-3/4"	42-1/16"	7.1	25.0
P406	6'	8'	28-1/4"	54-3/4"	10.1	33.5
P408	8'	10'	31-3/4"	79-1/2"	20.3	45.5
						TYPE U
**	** 3		DS.	LOAD CAPA	CTTY	TYPE IA DUTY RATING
★★ P410	** 3	12'	DS. 35-1/4"	10AD CAPA 79-3/8"	20.3	
			DS.			DUTY RATING

DIMENSIONS

Platform:	12-5/8" x 15"	Steps:	3" wide
Front Rails:	3-1/8" wide	Rear Rails:	1-3/4" wide
Front Flange:	1-1/8" wide	Rear Flange:	1" wide