



## THREADED FITTINGS

### 1/4"-28 Taper Thread Fittings

ALEMITE 1/4"-28 Taper Thread Fittings are used on most cars and trucks, as well as many industrial machines. It is recommended that SAE-LT taper threads be assembled into 1/4"-28 UNF, Class 3B, straight threaded holes having a modified maximum minor diameter of 0.2151", to ensure 75% minimum thread height.

**FEATURES:**

- Exceeds 72 hour salt spray test
- Dirt excluding check ball
- Trivalent zinc plating
- RoHS compliant

| Product # | Type     | Hex Size | Overall Length | Shank Length |
|-----------|----------|----------|----------------|--------------|
| 1641-B    | Straight | 5/16"    | 35/64"         | 3/16"        |
| 1652-B    | Straight | 5/16"    | 11/16"         | 23/64"       |
| 1680-B    | Straight | 5/16"    | 31/32"         | 5/8"         |
| 1698-B    | Straight | 5/16"    | 1-1/8"         | 25/32"       |
| 3014-B    | Straight | 5/16"    | 1-5/8"         | 1"           |
| 1637-B1   | 45°      | 3/8"     | 13/16"         | 13/64"       |
| 3010-B1   | 65°      | 3/8"     | 25/32"         | 19/64"       |
| 1911-B1   | 90°      | 3/8"     | 3/4"           | 13/64"       |

