

PROFESSIONAL PUNCHLOCK®

SINGLE SIDED STEPLADDER

FIBREGLASS

ELECTRO-SAFE™
& SUPER STRONG

**INDUSTRIAL
PROFESSIONAL**

150KG



- Punchlock® tread design and deep fascia top caps increase torsional rigidity of the overall ladder frames
- Strong, fibreglass construction with triangular plate bracing
- Internal spreader arms, heavy duty steel - cross braced. Available on models 1.8 to 3.6m
- Anti-slip rubber "Boots" for maximum grip on any surface and protection of the stiles
- Made to Australian and New Zealand Standards AS/NZS 1892.3

Product No.	Description	Ladder Size	Reach Height	EAN Code	Weight
FS10490	Pro FG RFSS 3 150kg	0.9m (3')	2.3m	9312097008168	4.5kg
FS10491	Pro FG RFSS 4 150kg	1.2m (4')	2.6m	9312097008175	5.5kg
FS10492	Pro FG RFSS 6 150kg	1.8m (6')	3.2m	9312097008182	8.8kg
FS10493	Pro FG RFSS 7 150kg	2.1m (7')	3.5m	9312097008199	9.8kg
FS10494	Pro FG RFSS 8 150kg	2.4m (8')	3.8m	9312097008205	11.6kg
FS10495	Pro FG RFSS 10 150kg	3.0m (10')	4.4m	9312097008212	17.1kg
FS10496	Pro FG RFSS 12 150kg	3.6m (12')	5.0m	9312097008229	20.9kg

PROFESSIONAL PUNCHLOCK®

DOUBLE SIDED STEPLADDER

FIBREGLASS

ELECTRO-SAFE™
& SUPER STRONG

**INDUSTRIAL
PROFESSIONAL**

150KG



- Punchlock® tread design and deep fascia top caps increase torsional rigidity of the overall ladder frames
- Strong, fibreglass construction with triangular plate bracing
- Double sided for greater versatility and greater load bearing strength
- Interlocking top caps adds strength and stability
- Internal spreader arms, heavy duty steel - cross braced available on models 1.8 to 3.6m
- Anti-slip rubber "Boots" for maximum grip on any surface and protection of the stiles
- Made to Australian and New Zealand Standards AS/NZS 1892.3

Product No.	Description	Ladder Size	Reach Height	EAN Code	Weight
FS10483	Pro FG DS3 150kg	0.9m (3')	2.3m	9312097007178	5.5kg
FS10484	Pro FG DS4 150kg	1.2m (4')	2.6m	9312097007185	7.0kg
FS10485	Pro FG DS6 150kg	1.8m (6')	3.2m	9312097007192	10.6kg
FS10486	Pro FG DS7 150kg	2.1m (7')	3.5m	9312097008058	12.5kg
FS10487	Pro FG DS8 150kg	2.4m (8')	3.8m	9312097008076	14.5kg
FS10488	Pro FG DS10 150kg	3.0m (10')	4.4m	9312097008083	20.3kg
FS10489	Pro FG DS12 150kg	3.6m (12')	5.0m	9312097008090	25.5kg

6300AZ SERIES

FIBREGLASS SINGLE SIDED STEPLADDER



150kg LOAD RATING

**HEAVY INDUSTRIAL
DUTY RATING**



- HolsterTop® - multi-function top
- Double riveted, slip-resistant TRACTION-TRED® steps
- Back-up plates reinforce all top connectors
- Heavy duty internal spreaders
- Slip-resistant foot pads riveted to the EDGE® structure
- The EDGE® moulded brace and foot pad combination provides enhanced strength and increased protection against damage
- Made to Australian and New Zealand Standards AS/NZS 1892.3

Product No.	Description	Ladder Size	Reach Height	EAN Code	Weight
6306AZ	FG SS 6 150KG	1.8m (6')	3.2m	0051751114591	9.98kg
6308AZ	FG SS 8 150KG	2.4m (8')	3.8m	0051751114607	13.6kg
6310AZ	FG SS 10 150KG	3.0m (10')	4.4m	0051751114614	17.7kg

T6300AZ SERIES

FIBREGLASS DOUBLE SIDED STEPLADDER



150kg LOAD RATING

**HEAVY INDUSTRIAL
DUTY RATING**



- High performance dual HolsterTop® paint and tool holder
- 4 rivets attach top to each rail
- Double riveted, slip-resistant TRACTION-TRED® steps
- Heavy duty internal spreaders
- All steps are knee-braced
- The EDGE® moulded brace and foot pad combination provides enhanced bracing strength and increased protection against damage
- Slip-resistant foot pads attached to the EDGE® structure
- Energy Diffusing Geometry
- Every rivet backed up by metal, metal plates or washers to protect rails
- Maximum load, including person and materials, shall not exceed Load Rating of ladder
- Made to Australian and New Zealand Standards AS/NZS 1892.3

Product No.	Description	Ladder Size	Reach Height	EAN Code	Weight
T6303AZ	FG DS 3 150KG	0.9m (3')	2.3m	0051751114539	7.25kg
T6304AZ	FG DS 4 150KG	1.2m (4')	2.6m	0051751114546	8.62kg
T6306AZ	FG DS 6 150KG	1.8m (6')	3.2m	0051751114553	12.25kg
T6308AZ	FG DS 8 150KG	2.4m (8')	3.8m	0051751114560	16.78kg
T6310AZ	FG DS 10 150KG	3.0m (10')	4.4m	0051751114577	24.72kg
T6312AZ	FG DS 12 150KG	3.6m (12')	5.0m	0051751114584	31.07kg