

Dimensions shown may be changed without prior notice

## // THERMOPLASTIC

### // MINIMESS



#### PRESSURE TEST POINT

**Tube:** polyester.

**Reinforcement:** one high tensile steel braid.

**Cover:** abrasion, ozone and hydrocarbon resistant polyurethane, pin-pricked.

**Application:** high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water. Specially designed for pressure gauges and transducers connections.

**Constant operation:** -40 °C +100 °C (-40 °F +212 °F)  
air max T = +70 °C (+160 °F)

**Length:** random

Item Code	↔			↔		↻		↻		⤴		⚙	
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1000310	01	2,0	5/64"	5,00	0,20	63,0	9100	190,0	27300	20,0	0,79	0,020	0,02

### // FLEXOR 7



#### SAE 100 R7 - EN 855 R7

**Tube:** polyester.

**Reinforcement:** one/two high tensile textile braids.

**Cover:** abrasion, ozone and hydrocarbon resistant polyurethane, pin-pricked.

**Application:** high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.

**Constant operation:** -40 °C +100 °C (-40 °F +212 °F)  
air max T = +70 °C (+160 °F)

**Length:** random

Item Code	↔			↔		↻		↻		⤴		⚙	
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1000290	03	5,0	3/16"	9,60	0,38	21,0	3000	84,0	12000	25,0	0,98	0,060	0,05
1000291	04	6,0	1/4"	12,20	0,48	21,0	3000	84,0	12000	35,0	1,38	0,100	0,07
1000292	05	8,0	5/16"	14,30	0,56	19,0	2750	76,0	11000	45,0	1,77	0,130	0,09
1000293	06	10,0	3/8"	16,00	0,63	16,0	2320	64,0	9280	55,0	2,17	0,145	0,10
1000294	08	13,0	1/2"	20,30	0,80	14,0	2000	56,0	8000	75,0	2,95	0,220	0,15