

**// FLEXOR 7 - TWIN**



**SAE 100 R7 - EN 855 R7**

**Tube:** polyester.  
**Reinforcement:** one/two high tensile textile braids.  
**Cover:** abrasion, ozone and hydrocarbon resistant polyurethane, pin-pricked.  
**Application:** high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.  
**Constant operation:** -40 °C +100 °C (-40 °F +212 °F)  
 air max T = +70 °C (+160 °F)  
**Length:** random

Item Code	↔			↔		↻		↻		⤴		⚖	
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1000298	04	6,0	1/4"	12,20	0,48	21,0	3000	84,0	12000	35,0	1,38	0,200	0,14
1000299	05	8,0	5/16"	14,30	0,56	19,0	2750	76,0	11000	45,0	1,77	0,260	0,18
1000300	06	10,0	3/8"	16,00	0,63	16,0	2320	64,0	9280	55,0	2,17	0,290	0,20
1000301	08	13,0	1/2"	20,30	0,80	14,0	2000	56,0	8000	75,0	2,95	0,440	0,30

**// FLEXOR 8**



**SAE 100 R8 - EN 855 R8**

**Tube:** polyester.  
**Reinforcement:** one/two braids of aramid fiber.  
**Cover:** abrasion, ozone and hydrocarbon resistant polyurethane, pin-pricked.  
**Application:** high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.  
**Constant operation:** -40 °C +100 °C (-40 °F +212 °F)  
 air max T = +70 °C (+160 °F)  
**Length:** random

Item Code	↔			↔		↻		↻		⤴		⚖	
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1000295	04	6,0	1/4"	11,50	0,45	35,0	5000	140,0	20000	50,0	1,97	0,085	0,06
1000483	05	8,0	5/16"	13,40	0,53	30,0	4300	120,0	17450	55,0	2,17	0,105	0,08
1000296	06	10,0	3/8"	15,50	0,61	28,0	4000	112,0	16000	60,0	2,36	0,135	0,10
1000416	08	13,0	1/2"	19,90	0,78	24,5	3500	98,0	14000	80,0	3,15	0,200	0,14