Barflex PVC Suction Hose TECHNOL



Barfell Product Code

Nominal in mm's

I.D. 0.D.

Vacuum Rating KPa/20°C

Working Pres. @ 20°C Mpa P.S.I.

Weight Kg/m

Min Bend Radius in mm

Coil Lengths in Metres

20

CLEAR BLACK

AIRSEEDER



A medium duty flexible PVC suction/discharge hose reinforced with a black spiral. It has a mirror smooth bore to minimise friction losses and is UV light stabilised.

207055	25.2	31.4	-90.0	0.8	116	0.34	120	20
207060	31.7	38.4	-90.0	0.7	102	0.47	150	20
207065	37.8	45.4	-90.0	0.6	87	0.62	200	20
207070	44.8	52.0	-90.0	0.6	79	0.70	240	20
207075	50.8	60.0	-90.0	0.5	72	0.93	300	20
207080	64.2	73.8	-90.0	0.5	72	1.43	400	20
207085	76.0	87.4	-90.0	0.4	58	2.02	450	20

Colour Clear with Black Rigid PVC Spiral

Applications Suitable for primary, secondary and tertiary lines on air seeder machines.

Temperature Range Flexibility

-5°C to +60°C Excellent

Chemical Resistance Good Abrasion Resistance Excellent

0.73

100

LPG VENT LIGHT DUTY



A highly flexible hose manufactured to AS1425 Section 2.2 covering LPG fuel systems for vehicle engines


206030 50.0 -90.0 60.8 0.3 36

Applications Suitable for use in converting cars, trucks and forklifts from petrol to gas.

Colour

Black

ODORFREE SANITATION HOSE





206670 25.0 32.0 -90.0 0.70 102 120 20 206680 38.4 46.2 -90.0 0.90 130 0.71 200 20

A highly flexible suction/discharge hose designed specifically for Spa operations.

0.7

0.6

0.5

100

85

75

Applications Suitable for use in all pressure or vacuum toilet systems

-90.0

-90.0

-90.0

Colour Beige

Chemical Resistance Excellent **Flexibility** Good

BARFLEX



Applications Flexible plumbing line used in spa's.

33.5

48.3

60.5

Chemical Resistance Flexibility

25.0

41.5

50.8

206270

206275

206280

Excellent Good

SPA HOSE



Custom Lengths Available

0.58

0.75

1.25

120

220

270

20

20

20