


BUTTWELD LONG RADIUS ELBOW 180 DEGREE (STD)

AAP CODE	IMPERIAL SIZE	A	B	C	D	WALL THICKNESS
WE20U	3/4	26.7	20.9	28.4	76.2	2.9
WE94U	1	33.4	26.6	38.1	76.2	3.4
WE25U	1 1/4	42.2	35	47.8	95.6	3.6
WE32U	1 1/2	48.3	40.9	57.2	114.4	3.7
WE40U	2	60.3	52.5	76.2	152.4	3.9
WE50U	2 1/2	73	62.6	95.2	190.4	5.2
WE65U	3	88.9	77.9	114.3	228.6	5.5
WE80U	4	114.3	102.3	152.4	304.8	6.1



BUTTWELD EQUAL TEE (STD)

AAP CODE	IMPERIAL SIZE	A	B	C	WALL THICKNESS
WT15	1/2	22	15.7	25	2.9
WT20	3/4	26.7	20.9	28.4	2.9
WT25	1	33.4	26.6	38.1	3.4
WT32	1 1/4	42.2	35	47.8	3.6
WT40	1 1/2	48.3	40.9	57.2	3.7
WT50	2	60.3	52.5	63.5	3.9
WT65	2 1/2	73	62.6	76.2	5.2
WT80	3	88.9	77.9	85.9	5.5
WT94	4	114.3	102.3	104.6	6.1
WT95	5	141.3	128.1	124	6.6
WT96	6	168.3	154.1	142.7	7.1
WT98	8	219.1	202.7	177.8	8.2
WTX25	10	273.1	254.5	215.9	9.3
WTX30	12	323.9	304.9	254	9.5
WTX35	14	355.6	336.5	279	9.5
WTX40	16	406.4	387.3	305	9.5
WTX45	18	457	437.9	343	9.5
WTX60	24	610	590.9	432	9.5