

// 740AA



Concrete pumping 85 bar (1275 psi) - Heavy duty - Steel reinforced

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile steel cords.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: high pressure concrete pumping.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		%	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in		kg/m	lb/ft
51,0	2"	69,00	2,72	85	1275	170	2500	255,0	10,04		2,100	1,42
63,0	2 1/2"	85,00	3,35	85	1275	170	2500	315,0	12,40		3,300	2,22
76,0	3"	100,00	3,94	85	1275	170	2500	380,0	14,96		4,490	3,02
90,0	3 1/2"	116,00	4,57	85	1275	170	2500	450,0	17,72		5,430	3,65
102,0	4"	126,00	4,96	85	1275	170	2500	510,0	20,08		6,520	4,39
127,0	5"	153,00	6,02	85	1275	170	2500	635,0	25,00		9,720	6,54
152,0	6"	184,00	7,24	85	1275	170	2500	760,0	29,92		13,660	9,19

// 741AA



Concrete pumping 100 bar (1500 psi) - Extra service - Steel reinforced

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile steel cords.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: high pressure concrete pumping.

Designed for long service life in heavy duty applications.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		%	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in		kg/m	lb/ft
51,0	2"	69,00	2,72	100	1500	200	2900	255,0	10,04		2,570	1,73
63,0	2 1/2"	85,00	3,35	100	1500	200	2900	315,0	12,40		3,750	2,53
76,0	3"	100,00	3,94	100	1500	200	2900	380,0	14,96		4,950	3,33
90,0	3 1/2"	116,00	4,57	100	1500	200	2900	450,0	17,72		7,190	4,84
102,0	4"	128,00	5,04	100	1500	200	2900	510,0	20,08		7,630	5,13
127,0	5"	155,00	6,10	100	1500	200	2900	635,0	25,00		10,220	6,87