

Dimensions shown may be changed without prior notice

// 265TH



Water-slurry S&D - PVC - Standard duty - Super elastic

Construction: light blue PVC with helical red stripe - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: water suction and delivery.

Special light weight construction for slurry tankers.

Good flexibility at low temperature.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⤴		⚠		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"			5	75	15	225	204,0	8,03	90	0,860	0,58	
63,0	2 1/2"			4	60	12	180	252,0	9,92	90	1,265	0,86	
76,0	3"			4	60	12	180	304,0	11,97	90	1,515	1,02	
102,0	4"			3	45	9	135	408,0	16,06	90	2,220	1,50	
127,0	5"			3	45	9	135	508,0	20,00	90	3,230	2,18	
152,0	6"			2	30	6	90	608,0	23,94	90	4,140	2,79	

// 267BE



Water-slurry S&D - PVC - Medium duty - Super elastic

Construction: grey PVC with helical blue stripe - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: water suction and delivery.

Special construction for slurry tankers.

Good flexibility at low temperature.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⤴		⚠		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
25,0	1"			7	100	21	300	100,0	3,94	90	0,415	0,28	
32,0	1 1/4"			7	100	21	300	128,0	5,04	90	0,605	0,41	
38,0	1 1/2"			7	100	21	300	152,0	5,98	90	0,705	0,48	
51,0	2"			5	75	15	225	204,0	8,03	90	1,000	0,68	
60,0	2 3/8"			5	75	15	225	240,0	9,45	90	1,280	0,87	
63,0	2 1/2"			5	75	15	225	252,0	9,92	90	1,340	0,91	
76,0	3"			5	75	15	225	304,0	11,97	90	1,750	1,18	
80,0	3 1/8"			5	75	15	225	320,0	12,60	90	1,840	1,24	
90,0	3 1/2"			4	60	12	180	360,0	14,17	90	2,260	1,52	
102,0	4"			4	60	12	180	408,0	16,06	90	2,700	1,82	
110,0	4 5/16"			4	60	12	180	440,0	17,32	90	3,100	2,09	
120,0	4 3/4"			4	60	12	180	480,0	18,90	90	3,600	2,42	
127,0	5"			4	60	12	180	508,0	20,00	90	3,800	2,56	
152,0	6"			3	45	9	135	608,0	23,94	90	4,850	3,26	
203,0	8"			3	45	9	135	812,0	31,97	90	9,100	6,12	