

PUR (Polyurethane) Vulcano Ducting

PUR (Polyurethane) Vulcano Ducting

Colour: Very clear with coppered steel spiral.

Working Temperature: - 40 °C to + 90 °C

Features: Clear with a copper coated steel wire. This ducting has a high resistance to abrasion, 5 times superior to that of PVC. Lightweight and extremely flexible.

Applications: Suction and discharge of abrasive powders, fumes, shavings, vapours in heavy-duty industrial applications.

SIDE DIA	WEIGHT	MIN WALL THICKNESS	BENDING RADIUS	VACUUM	ROLL LENGTH	
mm	Inch	(mm)	(mm)	(m/H2O)	(mtrs)	
51	2"	250	0,4	40	2	10
57		300	0,4	50	1,7	10
63		310	0,4	55	1,7	10
76	3"	510	0,45	65	1,7	10
90	3½"	610	0,45	75	1,6	10
102	4"	650	0,5	85	1,3	10
112		690	0,5	90	1,2	10
127	5"	850	0,5	105	1	10
152	6"	1040	0,55	125	0,8	10
180		1450	0,55	150	0,5	10
203	8"	1650	0,55	165	0,4	10
228	9"	1900	0,55	185	0,4	10
254	10"	2150	0,6	210	0,4	10
305	12"	2650	0,6	250	0,3	10
356	14"	3050	0,6	300	0,3	*
406	16"	3500	0,6	350	0,3	*

