

// 8K7AH

NEW

Autolock
Tube: oil resistant synthetic rubber.

Reinforcement: one high tensile textile braid.

Colours: black (conductive);

red, blue, yellow, green (non conductive).

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

Application: low pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.







Compatible with PUSH ON fittings.

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

air max T = +70 °C (+160 °F)

Safety factor: 4:1

Length: random

											
mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
6,0	1/4"	12,00	0,47	2,8	400	11,2	1620	65,0	2,56	0,105	0,08
10,0	3/8"	15,70	0,62	2,8	400	11,2	1620	75,0	2,95	0,150	0,11
13,0	1/2"	18,80	0,74	2,8	400	11,2	1620	100,0	3,94	0,200	0,14
16,0	5/8"	23,20	0,91	2,4	350	9,6	1400	125,0	4,92	0,270	0,19
19,0	3/4"	27,20	1,07	2,1	300	8,4	1200	150,0	5,91	0,400	0,27
25,0	1"	33,50	1,32	1,7	250	6,8	986	203,0	7,99	0,490	0,33