

**SRST-72AZ MODEL**

**450kg** WORKING LOAD LIMIT (W.L.L.)

**STYLE: Steel Rolling Scaffold**



**DIMENSIONS**

Model No.	Approx. Width	Approx. Length	Approx. Height	Approx. Shipping Wt.
SRST-72AZ	0.75 m	1.87 m	1.9 m	65.09 kg

**COMPONENT DIMENSIONS**

Component	Quantity Included	Approx. Width	Approx. Length	Approx. Height
Frames	2	0.74 m	1.75 m	3.8 cm
Arm Braces	2	3.8 cm	1.88 m	45.4 cm
Plywood Deck	1	0.72 m	1.69 m	3.8 cm
Locking Castors	4	13 cm	25 cm	--

- Easy one-person assembly - no tools required for quick setup and tear down.
- 450 kg Workin Load Limit (W.L.L.) distributed evenly.
- Base pack: 1.8 m maximum deck height, 3.8 m maximum reach height.
- Two base packs with guard rail and outriggers: 3.6 m maximum deck height, 5.6 m maximum reach height.

**ACCESSORIES (AVAILABLE SEPARATELY)**

Model No.	Description	Approx. Width	Approx. Length	Approx. Height	Approx. Shipping Wt.
SRO-72-4AZ	Outrigger Kit	45.7 cm	52.7 cm	--	17.01 kg
SRG-72AZ	Guard Rail and Toeboard Kit	0.73 m	1.77 m	1.07 m	31.97 kg

Note: Outriggers and Guard Rails are required when working height reaches 2 m.