

34 Naxos Way Keysborough VIC 3173
Phone: 1300 305 200
Web: www.staraluminium.com.au
Email: enquire@staraluminium.com.au

ALUMINIUM
REGISTERED WITH WORKSAFE



**Complies To
Australian Standards**
AS/NZS 1576.1/3
Material Temper 6061-T6

★ *Scaffold Features:*



Toeboard



Adjustable Scaffold Castor



Grasper



Tray

WorkSafe plant numbers #V0520215
Load Rating 450kg



WorkSafe plant numbers #V1200761
Load rating 225kg

★ *The Allowable Platform Height For STAR Scaffolding is as Follows:*

Base Size (m)	Maximum platform height (m) No outrigger	300mm wide outriggers (both sides)
1.8 x 1.2	3.6	5.5
2.4 x 1.2	3.6	5.5
3.0 x 1.2	3.6	5.5
750mm	2.3	3.5
1.8 x 1.8	5.4	7.5

★ *Warning*

AN INCORRECTLY ERECTED SCAFFOLD CAN CAUSE SERIOUS INJURY OR DEATH.

* Further advice on the selection, use and inspection of scaffolds is given in AS 4576 Guidelines for Scaffolding.

* Guidance on the erection of fabricated hung scaffolds and suspended scaffolds is given in chapters 21 and 22 of this Guide.

All Parts Fully Welded

Tube Size 48mm x 4.7mm / Brace Size 48mm x 2.8mm

SCAFFOLDS