

Complies To Australian Standards

AS1657-2018 AS/NZS 1892.1:1996

AS/NZS 1170.0-2002

COMES WITH ENGINEERING CERTIFICATION Manufacturing

★ Product Details:



Front safety boom arm



Box section and channel supports



Checker plate



Adjustable castor



eight	Area	Total base length	Approx.weight
00mm 30	000x750mm	3480x750x2305mm	147kg
00mm 40	000x750mm	4480x750x2305mm	163kg
00mm 60	000x750mm	6480x750x2305mm	238kg
00mm 60	00x750mm	6995x750x2400mm	255kg
֡	00mm 30 00mm 40 00mm 60	00mm 3000x750mm 00mm 4000x750mm 00mm 6000x750mm	300mm 3000x750mm 3480x750x2305mm 30mm 4000x750mm 4480x750x2305mm 30mm 6000x750mm 6480x750x2305mm

** All material alloy temper 6061T6. 60mm x 40mm x 3mm RHS, 100mm x 40mm x 4mm Channel, 48mm x 4.7mm tube, 100mm step section, 67° angle & 3mm checker plate. Handrailing painted to safety yellow for high visibility. Stair handrail height 1000mm, 45 degree angle, 225mm stair section.

TRUCK ACCESS PLATFORMS