

TPR (Thermoplastic Rubber) Vulcano Ducting

TPR (Thermoplastic Rubber) Vulcano Ducting

Colour: Black

Working Temperature: - 50 °C to + 90 °C

Features: Flexible duct made of extruded thermoplastic rubber, reinforced with a galvanised steel spiral. Resistant to high temperature, chemicals, abrasion and good UV resistance.

Applications: Suction and discharge of air and air-carried solids in medium-duty industrial applications.

INSIDE DIA	WEIGHT	MIN WALL THICKNESS	BENDING RADIUS	VACUUM	ROLL LENGTH	
						mm
51	210	0,4	40	2	10	
63	260	0,4	55	1,7	10	
76	390	0,4	65	1,7	10	
90	450	0,4	75	1,6	10	
102	495	0,4	85	1,3	10	
110	610	0,4	90	1,2	10	
127	690	0,4	105	1	10	
152	910	0,4	125	0,8	10	
160	950	0,4	130	0,7	10	
180	1210	0,4	150	0,5	10	
203	1320	0,4	165	0,4	10	
228	1490	0,4	185	0,4	10	
254	1800	0,4	210	0,4	10	
305	2100	0,4	250	0,3	10	
356	2450	0,4	300	0,3	10	
406	2800	0,4	350	0,3	10	



We cut to length